

VALENTINO TOPCOATS

WAX & METALLIC TOPCOATS

DESCRIPTION:

A mixture of wax, resins, oils, pigments and fine metallic particles designed to increase the polish level on and give accent tones to plaster surfaces.

BASIC USES:

For interior use over Bel Marmo, Venezia, V-Finish, and Tadelakt.

COLOR:

Available in clear, brown, silver, copper, interference gold, and interference green.

PACKAGING:

Packaged in 16 oz (68 g) wide mouth jars.

STORAGE:

1. Store containers in a cool, dry location.
2. Store at a temperature between 45°F (7°C) and 85°F (30°C).
3. Store out of direct sunlight.
4. Protect containers from weather and other damage.

COVERAGE:

Approximately 100ft² to 600 ft² in a one coat application. Coverage may vary due to ambient temperature, surface temperature, surface porosity, and/or application method.

SURFACE PREPARATION:

All surfaces to receive application must be free of debris, dust and dirt, grease, oils, curing agents, and cleaning solutions. Ensure that all surfaces are smooth and free of irregularities. Repair all cracks with the appropriate patching material for the existing substrate. Plaster finish must be cured a minimum of 24 hours prior to application of topcoat.

MIXING:

Material is premixed.

APPLICATION:

Valentino Topcoats may be applied with a clean white cotton cloth or a clean Omega-Pavan trapezoid trowel. To increase the topcoat's sheen, the topcoats may be buffed using a clean cotton cloth or buffer with suitable cotton pad after the wax has dried.

DRYING:

Allow to dry for 1 hour.

LIMITATIONS:

DO NOT apply product when the ambient and surface temperature is below 45°F (7°C) or above 85°F (30°C). Material that is allowed to freeze may suffer irreparable damage.

DO NOT use in constantly wet areas.

DO NOT add any other materials to the mixture of the product without written approval from Omega Products International, Inc.

DO NOT deviate in the mixing or application procedures contained in this, or any other Valentino Product Data Sheet, without written approval from Omega Products International, Inc.

DO NOT apply if there are contaminants on the receiving surface. Contaminates may include, but are not limited to, dust, debris, efflorescence, and/or oils.

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.



LIMITATIONS (CONT.):

Due to job conditions beyond the control of Omega Products International, Inc. we make no warranty as to the acceptance of the final color. The actual integrally colored finish should be applied on a sample section of the project and verified for color accuracy prior to the actual application process.

CLEANING:

Cleaning may be accomplished with water immediately after use.



SAFETY:

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

DISCLAIMER:

Omega Products International, Inc. [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

CLAIMS:

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.

TECHNICAL ASSISTANCE:

Technical assistance and information is available by calling Omega Products International, Inc. at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at info@omega-products.com.

WARRANTY:

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.