

V FINISH

A 100% ACRYLIC INTERIOR POLISHED FINISH PLASTER

DESCRIPTION:

V Finish is a 100% acrylic, interior polished finish plaster that provides a dependable, low maintenance finish, with an astonishing rich appearance.

BASIC USES:

V Finish is designed to be used as an interior colored polished plaster that can be troweled to achieve a high gloss look.

COLOR:

V Finish is colored using Valentino Color Bottles. See the Valentino Color Bottle Data Sheet for more information.

PACKAGING:

V Finish is packaged in 1-gallon (3.7L) and 3.5-gallon (13.2L) pails.

STORAGE:

1. Store containers in a cool, dry location.
2. Store at a temperature between 40°F (4°C) and 90°F (32°C).
3. Do not store in direct contact with the ground and/or concrete.
4. Store out of direct sunlight.
5. Protect containers from weather and other damage.

COVERAGE:

The coverage of V Finish is approximately 500 ft² (46.4m²) per gallon in a two-coat application. Coverage may vary due to surface ambient temperature, surface porosity, application thickness and/or application methods.

AREA OF USE:

V Finish must be applied to the V Base Coat. See the V Base data sheet for additional information.

SURFACE PREPARATION:

V Base Coat must be clean and free of debris, dirt, dust, efflorescence, grease, oils, curing agents, and cleaning solutions. Ensure that all surfaces are smooth and free of any irregularities. Repair all surface irregularities with the appropriate patching material for the existing substrate.

MIXING:

Mix materials to ensure colorants are uniformly dispersed. If necessary, dilute with small amount of clean potable water. Mix with clean tools and protect against entry of dust and debris.

APPLICATION:

1. Use a Venetian trowel to apply the V Finish at a 30° angle to ensure a thin layer to the properly prepared surface.
2. Multiple layers can be applied depending on the desired depth. Allow to fully dry between coats.
3. For the second coat, apply the finish at a 60° angle to ensure a thin layer. As before, use random strokes and remove any excess material. Multiple layers can be applied depending on the desired depth. Allow them to fully dry between coats.
4. Should sanding be required, use 800 or higher grit sandpaper.
5. To achieve a polished finish use a chrome steel trowel and lightly burnish the entire surface. For a high gloss finish V Wax may be applied.

DRYING:

Allow the product to dry for no less than 24 hrs. Drying time may vary due to ambient temperature, surface temperature, surface porosity, application method and/or thickness of material. All freshly applied material must be protected until fully dry. It is the responsibility of the applicator to determine if the product is fully cured and/or dry prior to exposing it to a condition that may be detrimental to the product.



LIMITATIONS:

DO NOT apply product when the ambient and surface temperature is below 40°F (4°C) or above 90°F (32°C). The ambient and surface temperature must stay consistently within this range until fully dry (see also DRYING).

DO NOT add any other materials to the mixture of the product without written approval from Omega Products International, Inc.

DO NOT deviate in the mixing or application procedures contained in this, or any other Valentino Product Data Sheets, without written approval from Omega Products International, Inc.

DO NOT apply V Finish if there are contaminants on the receiving surface. Contaminates may include, but are not limited to, dust, debris, efflorescence, and/or oils.

DO NOT use a Jiffler-type mixer that exceeds 500 RPM.

DO NOT use V Finish externally or expose it to continuous moisture.

CLEANING:

Cleaning may be accomplished with water immediately after use.

NOTE: Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

Due to job conditions beyond the control of Omega Products International, Inc. we make no warranty as to the acceptance of the final color. The actual integrally colored finish should be applied on a sample section of the project and verified for color accuracy prior to the actual application process.



SAFETY:

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

DISCLAIMER:

Omega Products International, Inc. [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

CLAIMS:

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.

TECHNICAL ASSISTANCE:

Technical assistance and information is available by calling Omega Products International, Inc. at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at info@omega-products.com.

WARRANTY:

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.