

# VENEZIA

A SMOOTH POLISHED LIME PLASTER FINISH

## DESCRIPTION:

Venezia Finish is a unique blend of marble dust, slaked aged lime, and other materials for the authentic Venetian plaster polished finish. When applied in layers, Venezia Finish creates a rich color variation that gives the perception of depth. It is designed to achieve a variety of finished looks while maintaining its workability and performance.

## BASIC USES:

Venezia can be applied over properly prepared plaster and gypsum board interior walls and ceilings. It may be used over some special decorative features.

## COLOR:

Venezia is manufactured white in color and can be tinted with Omega's exclusive Valentino color bottles.

## PACKAGING:

Venezia is packaged in 1 gallon (3.8L), 5 kg (11 lb) and 5 gallon (18.9L), 25 kg (55 lb) pails.

## STORAGE:

1. Store containers in a cool, dry location.
2. Store at a temperature between 45°F (7°C) and 90°F (32°C).
3. Do not store in direct contact with the ground and/or concrete.
4. Store out of direct sunlight.
5. Protect containers from weather and other damage.

## COVERAGE:

Venezia yields approximately 750 ft<sup>2</sup> per 5 gallon pail and 150 ft<sup>2</sup> per 1 gallon pail in a three-coat application. Coverage may vary due to ambient temperature, surface temperature, surface porosity, mixing method, and/or application method.

## SURFACE PREPARATION:

All surfaces to receive application must be free of debris, dust and dirt, efflorescence grease, oils, curing agents, and cleaning solutions. Ensure that all surfaces are smooth and free of irregularities. Repair all cracks with the appropriate patching material for the existing substrate. Surface should be primed with Omega's Valentino Mineral Primer.

## MIXING:

1. Venezia Finish should be mixed using a Jiffler-type mixer.
2. If multiple pails are being used, intermix (box) pails to achieve color consistency.

## APPLICATION:

Apply when temperature is between 45°F (4°C) to 90°F (32°C).

### **1st Coat - Base Coat**

Using an Omega-Pavan trapezoid trowel, apply Venezia just thick enough to cover the primer and substrate. This coat should be thick enough to give a smooth plaster base over the complete area of the substrate.

### **2nd Coat - Texture**

After the first coat is dry to the touch, use an Omega-Pavan trapezoid trowel or spatula to apply a patch of material with a short stroke, then reverse direction and immediately remove the material applied. Only a translucent patch of Venezia should remain. Repeat until 100% of the substrate is covered.

### **3rd Coat - Texture**

After the second coat is dry to the touch, use an Omega-Pavan trapezoid trowel or spatula to apply a patch of material with a short stroke, then reverse direction and immediately remove the material applied. Only a translucent patch of Venezia should remain. Repeat until 100% of the substrate is covered.

Allow to dry, then burnish with an Omega-Pavan Trapezoid trowel or spatula. If desired, apply waxes or topcoats after 24 hours and sealers after 48 hours.

## DRYING:

Allow material to dry naturally. Do not force dry with heaters or fans. Protect from excess wind and direct sunlight while material is wet.



**LIMITATIONS:**

DO NOT apply product when the ambient and surface temperature is below 45°F (7°C) or above 90°F (32°C). The ambient and surface temperature must stay consistently within this range until fully dry (see also DRYING). Protect all work from inclement weather with an approved protective system until fully dry.

DO NOT add any other materials to the mixture of the product without written approval from Omega Products International, Inc.

DO NOT deviate in the mixing or application procedures contained in this, or any other Valentino Product Data Sheet, without written approval from Omega Products International, Inc.

DO NOT apply Venezia if there are contaminants on the receiving surface. Contaminates may include, but are not limited to, dust, debris, efflorescence, and/or oils.

DO NOT use a Jiffler-type mixer that exceeds 500 RPM.

**NOTE:**

Failure to follow manufacturer's written specifications could result in the following, but not limited to spalling, cracking, peeling, chipping, delamination, discoloration, wash off, and overall system failure.

Due to job conditions beyond the control of Omega Products International, Inc. we make no warranty as to the acceptance of the final color. The actual integrally colored finish should be applied on a sample section of the project and verified for color accuracy prior to the actual application process.

**CLEANING:**

Cleaning may be accomplished with water immediately after use.



**SAFETY:**

Avoid contact with eyes or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush immediately with running water for at least 15 minutes. Consult a physician immediately. Do not take internally. Be sure to provide adequate ventilation in enclosed areas. Use of an approved respirator is recommended.

KEEP OUT OF REACH OF CHILDREN

**DISCLAIMER:**

Omega Products International, Inc. [Manufacturer] MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE PRODUCT SOLD HEREIN. The recommendations, suggestions, statements and technical data are based on the best knowledge available to Manufacturer and are given for informational purposes ONLY and without any responsibility for their use. It is expressly understood and agreed, as a condition of the use of this product, that the buyer's sole and exclusive remedy for any claimed defective product against Manufacturer shall be the replacement of products actually proven to be defective. Handling and use of the products are beyond the control of Manufacturer; therefore, no warranty is made, expressed or implied, as to the results obtained from the use of the product or against any claims for infringement of patents resulting from use of the product. Under no circumstance shall Manufacturer be liable for incidental or consequential damages arising out of the use or the improper application of the product. Before applying the product, the user shall determine the suitability of the product for his/her independent use, assuming all risks and liability whatsoever in connection therewith. This writing constitutes a complete and exclusive statement of the understanding between Manufacturer and Buyer.

**CLAIMS:**

Any Claimant shall notify Manufacturer immediately in writing of any alleged defect in the material. Claimant will provide Manufacturer with a reasonable and exclusive opportunity to investigate and test for the alleged defect. For any claim that is not valid Claimant agrees to pay Omega's reasonable charges, including travel and labor associated with investigation of such claim.

**TECHNICAL ASSISTANCE:**

Technical assistance and information is available by calling Omega Products International, Inc. at (800) 600-6634 or FAX (951) 520-2594 or by e-mail at "info@omega-products.com".

**WARRANTY:**

The following is made in lieu of all expressed and implied rights, warranties and conditions, statutory or otherwise. The manufacturer's only obligation shall be to replace such quantity of products proven to be defective within one year following the date of manufacture, provided that the alleged defective product is returned prepaid to the manufacturer's plant and is accompanied with proof of purchase and batch number.